

CENTRIFUGES

TABLE TOP LOW SPEED CENTRIFUGES



+27 60 999 9140

info@microanalytica.co.za

489 Jacqueline Drive, Garsfontein
Pretoria, Gauteng, 0081




ANALYTICAL EXCELLENCE...





www.microanalytica.co.za

Low Speed Centrifuge (Economical Type)

MODEL SPECIFICATIONS:

Model	Technical Parameters
<p>Model: TLS-HD Handle centrifuge, can be used for chemical-, biological-, hospital laboratories</p> 	<p>Capacity: 4*15ml Package size: 210*100*50mm Gross weight: 1.6 kg</p>
<p>Model: TLS-4KII Can be used for qualitative analysis and in biochemistry laboratories</p> 	<p>Max. Speed: 4000rpm, step adjusted speed Capacity: 20ml*6 Max. RCF: 1790xg Timing Range: 0~60min Power Supply: AC110/220V, 50/60Hz Package Size: 290*290*260mm Gross Weight: 4 kg</p>

<p>Model: TLS-H4KII Can be used in hospitals and biochemistry laboratories, to determine blood serum and blood plasma immunity</p>		<p>Speed Range: Starting ~4000rpm Capacity: 18*15ml Timing range: 0~30min Max. RCF: 2325xg Mechanical lock Power Supply: AC110/220V, 50/60Hz Package Size: 350*360*340mm Gross Weight: 10 kg</p>
<p>Model: TLS-4KA Can be used in hospitals and biochemical laboratories for qualitative analysis of serum, urea and plasma. Frame material: plastic with door switch</p>		<p>Max. Speed: 4000rpm Capacity: 8*20ml Max. RCF: 2325xg Timing Range: 0~30min Mechanical lock Power supply: AC110/220V, 50/60Hz Package Size: 350*360*340mm Gross Weight: 10 kg</p>
<p>Model: TLS-4K-2 Can be used for qualitative analysis</p>		<p>Max. speed: 4000rpm, step adjusted speed Capacity: 12*20ml Max. RCF: 2325xg Timing range: 0~60min With safety switch Power supply: AC110/220V, 50/60Hz Package Size: 380*330*310mm Gross Weight: 10 kg</p>

<p>Model: TLS-5K Characteristics: Large capacity, low noise, low temperature rise. Application: Biology, chemistry, medicine, pharmacy, food and environmental institutes. Separation of plasma or other suspension liquids</p>		<p>Max. speed: 5000rpm Max. RCF: 3600xg Capacity: 12*20ml Timing range: 0~30min Power supply: AC110/220V, 50/60Hz Package Size: 350*360*340mm Gross Weight: 10 kg</p>
<p>Model: TLS-4KB Application: Hospitals and biochemical laboratories for qualitative analysis of serum, urea and plasma. Frame material: plastic with door switch</p>		<p>Max. Speed: 4000rpm Max. RCF: 2325xg Capacity: 12*20ml Timing Range: 0~30min Power Supply: AC110/220V, 50/60Hz Package size: 350*360*340mm Gross weight: 10 kg</p>
<p>Model: TLS-4KC Application: Biology, chemistry, medicine, pharmacy, food and environmental institutes. Microprocessor control, driven by brushless motor and easy to operate With mechanical lock</p>		<p>Max. Speed: 4000rpm Max. RCF: 2325xg Angle Rotor Capacity: 20ml*12 Timing range: 0~99min Power Supply: AC110/220V, 50/60Hz Package Size: 350*360*340mm Gross Weight: 10 kg</p>
<p>Model: TLS-T4K Can be used in hospitals and bio-chemistry laboratories. Determination and analysis of blood serum etc. With safety switch</p>		<p>Speed Range: starting ~4000rpm Capacity: 8*20ml Timing Range: 0~30min Max. RCF: 2325xg Power Supply: AC110/220V, 50/60Hz Package Size: 380*330*310mm Gross Weight: 10 kg</p>

Model: TLS-H4K

Can be used in hospitals and bio-chemistry laboratories.

Determination and analysis of blood serum etc.

With mechanical lock



Speed Range: starting \sim 4000rpm

Capacity: 12*10ml

Timing Range: 0 \sim 30min

Max. RCF: 2325xg

Power supply: AC110/220V, 50/60Hz

Package Size: 350*360*340mm

Gross Weight: 10 kg