



ANALYTICAL EXCELLENCE...

+27 60 999 9140

info@microanalytica.co.za

489 Jacqueline Drive, Garsfontein
Pretoria, Gauteng, 0081

www.microanalytica.co.za

MicroPette Mechanical Pipette

FEATURES: MICROPETTE

- Light weight, ergonomic, low force design
- Digital display
- Volume range of 0.1 μ l to 10ml
- Easy to calibrate and maintain
- The lower part is Autoclavable
- Design helps to avoid repetitive strain injuries
- Manufactured from innovative materials



FEATURES: MULTI-CHANNEL MICROPETTE

- 8 and 12 channel pipettes are available for standard 96-well plate
- Dispensing head rotates ensure optimum pipetting convenience
- Individual piston/tip cone assemblies allow for easy repair and maintenance
- Compound material tip cone design allows visual seal verification
- Universal pipette tips can be used



MODEL SPECIFICATIONS:

Single-channel Adjustable Volume Pipettes							
Model No	Volume Range	Increment	Test Volume (μ l)	Maximum Permissible Systematic error		Maximum Permissible Random error	
				%	μ l	%	μ l
MM2.5	0.1-2.5 μ l	0.05 μ l	2.5	2.50%	0.0625	2.00%	0.05
			1.25	3.00%	0.0375	3.00%	0.0375
			0.25	12.00%	0.03	6.00%	0.015
MM10	0.5-10 μ l	0.1 μ l	10	1.00%	0.1	0.80%	0.08
			5	1.50%	0.075	1.50%	0.075
			1	2.50%	0.025	1.50%	0.015
MM20	2-20 μ l	0.5 μ l	20	0.90%	0.18	0.40%	0.08
			10	1.20%	0.12	1.00%	0.1
			2	3.00%	0.06	2.00%	0.04
MM50	5-50 μ l	0.5 μ l	50	0.60%	0.3	0.30%	0.15
			25	0.90%	0.225	0.60%	0.15
			5	2.00%	0.1	2.00%	0.1
MM100	10-100 μ l	1 μ l	100	0.80%	0.8	0.15%	0.15
			50	1.00%	0.5	0.40%	0.2
			10	3.00%	0.3	1.50%	0.15
MM20/200	20-200 μ l	1 μ l	200	0.60%	1.2	0.15%	0.3
			100	0.80%	0.8	0.30%	0.3
			20	3.00%	0.6	1.00%	0.2

MM50/200	50-200µl	1µl	200	0.60%	1.2	0.15%	0.3
			100	0.80%	0.8	0.30%	0.3
			50	1.00%	0.5	0.40%	0.2
MM100/1000	100-1000µl	5µl	1000	0.60%	6	0.20%	2
			500	0.70%	3.5	0.25%	1.25
			100	2.00%	2	0.70%	0.7
MM200/1000	200-1000µl	5µl	1000	0.60%	6	0.20%	2
			500	0.70%	3.5	0.25%	1.25
			200	0.90%	1.8	0.30%	0.6
MM5000	1000-5000µl	50µl	5000	0.50%	25	0.15%	7.5
			2500	0.60%	15	0.30%	7.5
			1000	0.70%	7	0.30%	3
MM10ml	2-10ml	0.1ml	10ml	0.60%	60	0.20%	20
			5ml	1.20%	60	0.30%	15
			2ml	3.00%	60	0.60%	12

8-channel Adjustable Volume Pipettes							
Model No	Volume Range	Increment	Test Volume (µl)	Maximum Permissible Systematic error		Maximum Permissible Random error	
				%	µl	%	µl
MM10/8	0.5-10µl	0.1µl	10	1.50%	0.15	1.50%	0.15
			5	2.50%	0.125	2.50%	0.125
			1	4.00%	0.04	4.00%	0.04

MM50/8	5-50µl	0.5µl	50	1.00%	0.5	0.50%	0.25
			25	1.50%	0.375	1.00%	0.25
			5	3.00%	0.15	2.00%	0.1
MM300/8	50-300µl	5µl	300	0.70%	2.1	0.25%	0.75
			150	1.00%	1.5	0.50%	0.75
			50	1.50%	0.75	0.80%	0.4

12-channel Adjustable Volume Pipettes							
Model No	Volume Range	Increment	Test Volume (µl)	Maximum Permissible Systematic error		Maximum Permissible Random error	
				%	µl	%	µl
MM10/12	0.5-10µl	0.1µl	10	1.50%	0.15	1.50%	0.15
			5	2.50%	0.125	2.50%	0.125
			1	4.00%	0.04	4.00%	0.04
MM50/12	5-50µl	0.5µl	50	1.00%	0.5	0.50%	0.25
			25	1.50%	0.375	1.00%	0.25
			5	3.00%	0.15	2.00%	0.1
MM300/12	50-300µl	5µl	300	0.70%	2.1	0.25%	0.75
			150	1.00%	1.5	0.50%	0.75
			50	1.50%	0.75	0.80%	0.4

Fixed Volume Pipettes							
Model No	Volume Range	Increment	Test Volume (μl)	Maximum Permissible Systematic error (Inaccuracy)		Maximum Permissible Random error (Inaccuracy)	
				%	μl	%	μl
MM5F	5 μl	-	5 μl	1.3%	0.065	1.2%	0.06
MM10F	10 μl	-	10 μl	0.8%	0.08	0.8%	0.08
MM20F	20 μl	-	20 μl	0.6%	0.12	0.5%	0.1
MM25F	25 μl	-	25 μl	0.5%	0.125	0.3%	0.075
MM50F	50 μl	-	50 μl	0.5%	0.25	0.3%	0.15
MM100F	100 μl	-	100 μl	0.5%	0.5	0.3%	0.3
MM200F	200 μl	-	200 μl	0.4%	0.8	0.2%	0.4
MM250F	250 μl	-	250 μl	0.4%	1.0	0.2%	0.5
MM500F	500 μl	-	500 μl	0.3%	1.5	0.2%	1.0
MM1000F	1000 μl	-	1000 μl	0.3%	3.0	0.2%	2.0
MM2000F	2000 μl	-	2000 μl	0.3%	6.0	0.15%	3.0
MM5000F	5000 μl	-	5000 μl	0.3%	15	0.15%	7.5