INCUBATORS



- +27 60 999 9140
- info@microanalytica.co.za
- ↑ 489 Jacqueline Drive, Garsfontein Pretoria, Gauteng, 0081

ANALYTICAL EXCELLENCE...

www.microanalytica.co.za

Climate Incubator MA-A100C / MA-A1500C

FEATURES:

- Shell is made of bronze aluminium alloy cold-rolled steel plate, tank body is made of mirror stainless steel
- Shelf bracket can be adjusted at will
- LCD display
- LED plant light system
- Specially designed air duct structure and air circulation design with breeze makes the indoor temperature and humidity control more stable and even
- A large volume tank ultrasonic humidifier, making humidification more reliable and stable
- The controller has a variety of anti-interference measures: the thermostat is equipped with sensor failure alarm, upper and lower temperature deviation alarm, over temperature alarm and parameter storage





MA-A1000C MA-A1500C

MODEL SPECIFICATIONS:

Model	MA-A1000C	MA-A1500C
Volume	1000L	1500L
Temp. Control Range	0~50°C	
Temp. Control Precision	±0.1°C	
Temp. Fluctuation Degree	±1°C (experimental conditions: no load, environmental temperature 20°C, humidity 50% RH)	
Humidity Range	50% ~ 95% RH	
Humidity Control Accuracy	±1% RH	
Humidity Control Fluctuation	±5% RH ~±7% RH	
Ambient Temp.	5~35°C	
Light (lux)	20000 lux	
Working Environment	10 ~30°C	
Time Setting	0~99 hours 59 minutes / continuous operation	
Power Supply	AC220V±10%, 50Hz (standard); AC110V±10%, 60Hz (optional)	
Consumption	1923W	3738W
Shelves	6	9
Number of Shelves	3	3
External Size (W*D*H) mm	1400*690*1980	2020*700*1980
Studio Size (W*D*H) mm	1300*640*1250	1960*640*1250
Package Size (W*D*H) mm	1500*820*2150	2160*900*2080
Gross Weight (kg)	200	350
Optional Equipment	* Led cold light lamp; * USB flash disk for data storage; * Microcomputer printing; * Carbon dioxide function; * Audible and visual alarm; * Over-temperature protection; * Timing air exchange function; * Remote alarm system; * 485 interface; * Multiple programming	
Note: Inform the manufacturer if	the temperature is below 5°C or above 42°C an	d/or the humidity is below 50% over an extended period